5

WHAT IS CLAIMED IS:

- 1. An amorphous composition comprising an amorphous matrix, a metal ion selected from the group consisting of Gd³⁺, Fe⁺³ and Mn⁺², and a ligand, said composition having a selected induced magnetization at cryogenic temperatures.
- 2. The composition of claim 1, wherein said ligand binds said metal ion and effects

solubility thereof in said amorphous matrix.

- The composition of claim 2, wherein said metal ion is Gd³⁺ and is in the form of Gd(Lg)₃ or, in the alternative, in the form of Gd(ACAc)_{3'} wherein Ac is acetylacetonate, and Lg is 2,2,6,6-tetramethyl-3, 5-heptanedionate.
 - 4. The composition of claim 1, wherein said amorphous matrix comprises epoxy resin.
- 15 5. The composition of claim 1, wherein said amorphous matrix comprises a glass.
 - 6. The composition of claim 1, wherein said amorphous matrix comprises a plastic.
- 7. The composition of claim 1, wherein said composition is characterized by magnetization equal to that of another selected material for exposure of both said materials by an applied magnetic field.
 - 8. The composition of claim 1, wherein said selected magnetic susceptibility is zero.
- 25 9. The composition of claim 1, wherein said selected magnetic susceptibility is reached at a selected temperature below substantially 77°K.
 - 10. The composition of claim 1, wherein said metal ion is Gd^{+3} .
- 30 11. A method of preparing an amorphous composition to exhibit a desired susceptibility at cryogenic temperatures, comprising the steps of:

mixing a metal ion selected from the group consisting of Gd³⁺, Fe⁺³ and Mn⁺², with an amorphous matrix and a ligand so that the resulting composition has a nearly zero magnetic susceptibility at said cryogenic temperatures.

Docket No. 03-03 US

10

25

- 12. The method of claim 11, wherein said ligand binds said metal ion and effects solubility thereof in said composition.
- The method of claim 11, wherein said metal ion is Gd and is in the form selected from the group consisting of Gd(Lg)₃ and Gd(AcAc)₃ wherein Ac is acetylacetonate, and Lg is 2,2,6,6-tetramethyl-3, 5-heptanedionate.
 - 14 The method of claim 11, wherein said amorphous matrix is epoxy resin.
 - 15. The method of claim 11, wherein said composition has a magnetization equal to the magnetization of another material in the presence of the same magnetic field.
- 16. An NMR apparatus comprising a magnet for producing a polarizing field and utilizing a composition subject to said polarizing field, said composition an amorphous comprising a selected amorphous material and a metal ion selected from the group consisting of Gd³⁺, Fe⁺³ and Mn⁺², and a ligand said composition having a selected value of magnetizationat cryogenic temperatures.
- 20 17. The NMR apparatus of claim 16, wherein said ligand binds said metal ion and effects solubility thereof in said composition.
 - 18. The NMR apparatus of claim 16, wherein said cryogenic temperatures are at or below 77° K.
 - 19. The NMR apparatus of claim 16, wherein said composition is surrounded by a material exhibiting a magnetization of zero and said selected value is zero.